



## DECLARATION OF PERFORMANCE

### No 032/IZOB/2026

1. Unique identification code of the product-type: **SBS-modified bitumen torch-on underlayer**  
**IZOBIT SUPER PV 3 FF**
2. Intended use:
  - a. **Damp proofing of buildings, including products for waterproofing of underground parts**
  - b. **Damp proofing of buildings, including products for waterproofing of underground parts subject to reaction to fire testing**
  - c. **Waterproofing of roofs, subject to reaction to fire testing**
  - d. **Waterproofing of roofs**
  - e. **Waterproofing of roofs, subject to external fire exposure testing**
  - f. **Vapour control products subject to fire reaction requirements**
  - g. **Vapour control products**
3. Manufacturer:  
**Izobud Sp. z o.o., ul. Leśna 4, Łąki Kozielskie, 47-150 Leśnica, Poland**
4. Systems of assessment and verification of constancy of performance:  
**System 2+ for application type: a, d System 3 for application type: b, c, e, f, g**
5. Harmonized standard:  
**EN 13707:2004+A2:2009; EN 13969:2004/A1:2006, EN 13969:2004; EN 13970:2004; EN 13970:2004/A1:2006**  
Notified body:  
**1023, 1488, 1454**
6. Declared performance:

<u>Essential characteristics</u>	<u>Performance characteristics</u>			<u>Harmonized standard</u>
Flexibility at low temperature	<b>≤ -16°C</b>			EN 13707:2004+A2:2009, EN 13969:2004/A1:2006, EN 13969:2004
Watertightness	(B method)		<b>60 kPa</b>	EN 13707:2004+A2:2009, EN 13969:2004/A1:2006, EN 13969:2004  EN 13707:2004+A2:2009, EN 13969:2004/A1:2006, EN 13969:2004 EN 13970:2004, EN 13970:2004/A1:2006
Reaction to fire			<b>class E</b>	
Resistance to static loading	(A method)		<b>5 kg</b>	
Resistance to impact	(A method)		<b>1000 mm</b>	
Tensile strength	max. tensile strength	longitudinal	<b>800 (± 300) N/50 mm</b>	
		transverse	<b>600 (± 300) N/50 mm</b>	
	elongation at max. tensile strength	longitudinal	<b>50 (±30) %</b>	
		transverse	<b>60 (±30) %</b>	
Joint strength	shear resistance	longitudinal overlap	<b>500 (± 300) N/50 mm</b>	
		transverse overlap	<b>700 (± 300) N/50 mm</b>	
	peel resistance	longitudinal overlap	<b>NPD</b>	
		transverse overlap	<b>NPD</b>	
Harmful substances	<b>does not contain</b>			
Resistance to tearing	nail	longitudinal	<b>250 (± 100) N</b>	
		transverse	<b>300 (± 100) N</b>	
Durability	flexibility at low temperature		<b>-9 (±3) °C</b>	
Water vapour transmission	Sd value		<b>~1500 m</b>	
Resistance to root penetration				EN 13970:2004, EN 13970:2004/A1:2006
Resistance to root penetration	<b>NPD</b>			EN 13707:2004+A2:2009
External fire performance	<b>Broof (t1); Broof(t2); Broof(t3)</b>			EN 13707:2004+A2:2009

7. The performance of the product above is in accordance with the declared product characteristics. The Declaration of Performance in accordance with Regulation (EU) No 305/2011 is the sole responsibility of the manufacturer named above.

In the name of the producer signed by:  
Mr. Joachim Sekler

»IZOBUD« Sp. z o.o.  
CZŁONEK ZARZĄDU  
*Joachim Sekler*

Łąki Kozielskie, 16.01.2026