



EXPERT IN MANUFACTURING BITUMEN MEMBRANES

## DECLARATION OF PERFORMANCE

### No 118/IZOB/2025

- Unique identification code of the product-type: **Self-adhesive SBS-modified bitumen underlayer**  
**IZOBIT SUPER STICK PV 2.0**
- Intended use:
  - Waterproofing of roofs**
  - Waterproofing of roofs, subject to external fire exposure testing**
  - Waterproofing of roofs, subject to reaction to fire testing**
  - Damp proofing of buildings, including products for waterproofing of underground parts**
  - Damp proofing of buildings, including products for waterproofing of underground parts subject to reaction to fire testing**
- Manufacturer:  
**Izobud Sp. z o.o., ul. Leśna 4, Łąki Kozielskie, 47-150 Leśnica, Poland**
- Systems of assessment and verification of constancy of performance:  
**System 2+ for application type: a, d System 3 for application type: b, c, e**
- Harmonized standard:  
**EN 13707:2004+A2:2009; EN 13969:2004/A1:2006; EN 13969:2004**  
Notified body:  
**1023, 1488, 1454**
- Declared performance:

<u>Essential characteristics</u>	<u>Performance characteristics</u>			<u>Harmonized standard</u>
Flexibility at low temperature			$\leq -25^{\circ}\text{C}$	EN 13707:2004+A2:2009, EN 13969:2004/A1:2006, EN 13969:2004
Watertightness	(method B)		<b>60 kPa</b>	
Reaction to fire			<b>class E</b>	
Resistance to static loading			<b>NPD</b>	
Resistance to impact			<b>NPD</b>	
Tensile strength	max. tensile strength	longitudinal	<b>600 (<math>\pm 200</math>) N/50 mm</b>	
		transverse	<b>450 (<math>\pm 200</math>) N/50 mm</b>	
	elongation at max. tensile strength	longitudinal	<b>50 (<math>\pm 20</math>) %</b>	
		transverse	<b>50 (<math>\pm 20</math>) %</b>	
Joint strength	shear resistance	longitudinal overlap	<b>NPD</b>	
		transverse overlap	<b>NPD</b>	
	peel resistance	longitudinal overlap	<b>NPD</b>	
		transverse overlap	<b>NPD</b>	
Harmful substances			<b>does not contain</b>	EN 13707:2004+A2:2009
Resistance to tearing	nail	longitudinal	<b>200 (<math>\pm 100</math>) N</b>	
		transverse	<b>200 (<math>\pm 100</math>) N</b>	
Durability			<b>NPD</b>	
Resistance to root penetration			<b>NPD</b>	EN 13707:2004+A2:2009
External fire performance			<b>Broof (t3)</b>	

- The performance of the product above is in accordance with the declared product characteristics. The Declaration of Performance in accordance with Regulation (EU) No 305/2011 is the sole responsibility of the manufacturer named above.

In the name of the producer signed by:  
Mr. Joachim Sekler

**»IZOBUD«** Sp. z o.o.  
CZŁONEK ZARZĄDU  
*Joachim Sekler*

Łąki Kozielskie, 10.04.2025