



DECLARATION OF PERFORMANCE

No 117/IZOB/2026

1. Unique identification code of the product-type: **Self-adhesive SBS-modified bitumen underlayer**
IZOBIT SUPER STICK GV3
2. Intended use:
 - a. **Damp proofing of buildings, including products for waterproofing of underground parts**
 - b. **Damp proofing of buildings, including products for waterproofing of underground parts subject to reaction to fire testing**
 - c. **Waterproofing of roofs, subject to reaction to fire testing**
 - d. **Waterproofing of roofs**
 - e. **Waterproofing of roofs, subject to external fire exposure testing**
 - f. **Vapour control products subject to fire reaction requirements**
 - g. **Vapour control products**
3. Manufacturer:
IZobud Sp. z o.o., ul. Leśna 4, Łąki Kozielskie, 47-150 Leśnica, Poland
4. Systems of assessment and verification of constancy of performance:
System 2+ for application type: a, d System 3 for application type: b, c, e, f, g
5. Harmonized standard:
EN 13707:2004+A2:2009; EN 13969:2004/A1:2006, EN 13969:2004; EN 13970:2004, EN 13970:2004/A1:2006
Notified body:
1023, 1488, 1454
6. Declared performance:

<u>Essential characteristics</u>	<u>Performance characteristics</u>			<u>Harmonized standard</u>
Flexibility at low temperature	≤-30°C			EN 13707:2004+A2:2009, EN 13969:2004/A1:2006, EN 13969:2004
Watertightness	(method B)			EN 13707:2004+A2:2009, EN 13969:2004/A1:2006, EN 13969:2004 EN 13970:2004, EN 13970:2004/A1:2006
Reaction to fire	class E			
Resistance to static loading	≥5 kg			
Resistance to impact	≥600 mm			
Tensile strength	max. tensile strength	longitudinal	600 (± 200) N/50 mm	
		transverse	450 (± 200) N/50 mm	
	elongation at max. tensile strength	longitudinal	6 (±4) %	
		transverse	6 (±4) %	
Joint strength	shear resistance	longitudinal overlap	450 (± 150) N/50 mm	
		transverse overlap	300 (± 150) N/50 mm	
	peel resistance	longitudinal overlap	NPD	
		transverse overlap	NPD	
Harmful substances	NPD			
Resistance to tearing	nail	longitudinal	150 (± 100) N	
		transverse	100 (± 50) N	
Durability	NPD			
Water vapour transmission	Sd value			EN 13970:2004, EN 13970:2004/A1:2006
Resistance to root penetration	NPD			EN 13707:2004+A2:2009
External fire performance	B_{roof} (t1); B_{roof} (t2); B_{roof} (t3)			EN 13707:2004+A2:2009

7. The performance of the product above is in accordance with the declared product characteristics. The Declaration of Performance in accordance with Regulation (EU) No 305/2011 is the sole responsibility of the manufacturer named above.

In the name of the producer signed by:
Mr. Joachim Sekler

»IZOBUD« Sp. z o.o.
CZŁONEK ZARZĄDU
Joachim Sekler

Łąki Kozielskie, 16.01.2026