



DECLARATION OF PERFORMANCE

No 001/PET/2025

1. Unique identification code of the product-type: **Rubber-bitumen membrane for waterproofing roof insulation**
IZOBUD W-PET/SBS

2. Intended use or uses:

Waterproofing of roofs

3. Manufacturer:

Izobud Sp. z o.o., ul. Leśna 4, Łąki Kozielskie, 47-150 Leśnica, Poland

4. Systems of assessment and verification of constancy of performance:

System 2+, System 4

5. Harmonized standard:

EN 13707:2004+A2:2009

Notified body:

1023

6. Declared performance:

<u>Essential characteristics</u>		<u>Performance characteristics</u>		<u>Harmonized standard</u>
Watertightness	(method B)		10 kPa	EN 13707:2004+A2:2009
Reaction to fire			class E	
External fire performance			NPD	
Flexibility at low temperature			≤-17°C	
Resistance to root penetration			NPD	
Resistance to static loading			NPD	
Resistance to impact			NPD	
Tensile strength	max. tensile strength	longitudinal	480 (±150) N/50 mm	
		transverse	380 (± 150) N/50 mm	
	elongation at max. tensile strength	longitudinal	33 (± 15) %	
		transverse	40 (± 15) %	
Joint strength	shear resistance	longitudinal overlap	NPD	
		transverse overlap	NPD	
	peel resistance	longitudinal overlap	NPD	
		transverse overlap	NPD	
Harmful substances			does not contain	
Resistance to tearing	nail	longitudinal	250 (± 150) N	
		transverse	250 (± 150) N	
Durability		flexibility at low temperature	-15 (± 3)°C	

7. The performance of the product above is in accordance with the declared product characteristics. The Declaration of Performance in accordance with Regulation (EU) No 305/2011 is the sole responsibility of the manufacturer named above.

In the name of the producer signed by:

Mr. Joachim Sekler

»IZOBUD« Sp. z o.o.
CZŁONEK ZARZĄDU
Joachim Sekler

Łąki Kozielskie, 10.04.2025