



## DECLARATION OF PERFORMANCE No 079/IZOB/2025

- Unique identification code of the product-type: **Bitumen cap sheet  
W 400/1200**
- Intended use or uses:
  - Waterproofing of roofs, subject to reaction to fire testing**
  - Waterproofing of roofs**
- Manufacturer:  
**Izobud Sp. z o.o., ul. Leśna 4, Łąki Kozielskie, 47-150 Leśnica, Poland**
- Systems of assessment and verification of constancy of performance:  
**System 2+ for application type: b System 3 for application type: a**
- Harmonized standard:  
**EN 13707:2004+A2:2009**  
Notified body:  
**1023, 1454**
- Declared performance:

| <u>Essential characteristics</u> | <u>Performance characteristics</u>      |                      |                     | <u>Harmonized standard</u> |
|----------------------------------|---|----------------------|---------------------|----------------------------|
| Watertightness                   | (B method)                              |                      | 10 kPa              | EN 13707:2004+A2:2009      |
| Reaction to fire                 |   |                      | class E             |                            |
| External fire performance        |   |                      | NPD                 |                            |
| Flexibility at low temperature   |   |                      | ≤ 0°C               |                            |
| Resistance to root penetration   |   |                      | NPD                 |                            |
| Resistance to static loading     |   |                      | NPD                 |                            |
| Resistance to impact             |   |                      | NPD                 |                            |
| Tensile strength                 | max. tensile strength                   | longitudinal         | 400 (± 200) N/50 mm |                            |
|                                  |   | transverse           | 300 (± 200) N/50 mm |                            |
|                                  | elongation at max. tensile strength     | longitudinal         | 6 (± 4) %           |                            |
|                                  |   | transverse           | 6 (± 4) %           |                            |
| Joint strength                   | shear resistance                        | longitudinal overlap | NPD                 |                            |
|                                  |   | transverse overlap   | NPD                 |                            |
|                                  | peel resistance                         | longitudinal overlap | NPD                 |                            |
|                                  |   | transverse overlap   | NPD                 |                            |
| Harmful substances               |   |                      | does not contain    |                            |
| Resistance to tearing            | nail                                    | longitudinal         | NPD                 |                            |
|                                  |   | transverse           | NPD                 |                            |
| Durability                       | flow resistance at elevated temperature |                      | +70 (± 10)°C        |                            |

- The performance of the product above is in accordance with the declared product characteristics. The Declaration of Performance in accordance with Regulation (EU) No 305/2011 is the sole responsibility of the manufacturer named above.

In the name of the producer signed by:  
Mr. Joachim Sekler

»IZOBUD« Sp. z o.o.  
CZŁONEK ZARZĄDU  
Joachim Sekler

Łąki Kozielskie, 10.04.2025